

# Dot matrix displays

The Dot Matrix display option is available on many of AIC's latest range of instruments. The display will allow single or multi line display depending on the input type required and number of inputs. The flexibility of the display lends itself to many standard applications and to custom design products. The serial input display can be used as message display. The Binary input display can be used to show the Binary or BCD value or to display user configured messages.



## Features

- Wide range of input options including:
  - Multi channel 4-20mA
  - Multi channel thermocouple or RTD
  - Serial input, RS232, RS485, RS422,
  - Serial current loop
  - Load cells/pressure sensors
  - Conductivity or Resistivity or PPM
  - pH or ORP plus temperature
  - Binary or BCD
- Ethernet, CAN BUS, RS232, RS485 communications
- Scalable displays with user selectable unit and channel names (via supplied PC software)
- Backlit display
- IP65 rated wall mount enclosure
- 2 year guarantee



User configurable  
input names and units

DMDISP-1.0-0

**AMALGAMATED INSTRUMENT CO PTY LTD**

ACN: 001 589 439

Unit 5, 28 Leighton Place Hornsby  
NSW 2077 Australia

Telephone: +61 2 9476 2244  
Facsimile: +61 2 9476 2902

e-mail: sales@aicpl.com.au  
Internet: www.aicpl.com.au